

Product Information



MHDTV



Deployed Dimensions

Deployed: 34.25" High
Deployed: 21" Wide
Deployed: 35.25" Long

Stowed Dimensions

Stowed: 10.5" High
Stowed: 21" Wide
Stowed: 35.25" Long

TECHNICAL SPECIFICATIONS

REFLECTOR TYPE

20" Effective area, elliptical offset

MAXIMUM MOUNT ROTATION

Elevation: 145°
 Azimuth: 375°
 Skew (Polarization): +-55°
 Max look angle at: +75°

MOTOR

3-Motor Axis: Elevation, Azimuth, Skew
 Typical Motor Voltage: .7 Amps
 Surge Motor Voltage: 1.2 Amps

SPEED

Deploying Elevation: 10° per second
 Deploying Azimuth: 12° per second
 Peaking: 12° per second
 (Acquisition time is 2 to 4 minutes typical)

DIMENSIONS OF DISH

Length (Stowed): 35.25 Inches
 Width (Stowed): 21 Inches
 Height (Stowed): 10.5 Inches
 Weight: 35 lbs

CABLING

Wired for 2 RG6
 Control Cable: [9 conductor 22AWG 30']

ENVIRONMENT

Wind Deployed: 60 mph
 Wind Stowed: 140 mph
 Temperature: Operational from -20°F to 125°F

CONTROLLER

Nomad, Nomad 2 Universal DVB Controller
 DVB Tuner: Yes
 Software: Embedded
 Controller Voltage: 12V DC 4 Amp
 Receiver Compatibility: Any High Definition
 DirecTV Receiver

YOUR AUTHORIZED DEALER / INSTALLATION PROVIDER IS:



Montana Satellite
"we do dishes"
 Phone: 406-756-0200
 Fax: 781-459-0330
www.montanasatellite.com